



A1 Akrilik Macun

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Su bazlı akrilik reçine esaslı bir macundur.

FEATURES

- İç ve dış cephede kullanılır.
- Çatlak onarımında ya da oluşumunun engellemesi amacıyla kullanılır.

SURFACE PREPARATION

Uygulama yapılacak olan yüzey önce temizlenerek tozdan arındırılır ve su ile yıkanır. Çatlaklar (V) şeklinde açıldıktan sonra temizlenir ve zemin su ile nemlendirilir.

APPLICATION

Çatlaklar çelik mala yardımıyla uygulanır. Çok geniş çatlaklarda veya yarık doldurmada uygulama iki defada tamamlanır.

Katlar arası 12 saat beklenmelidir.

Derin çukur ve yarıkların tamiratı için A1 Akrilik Macuna uygulama kıvamını etkilemeyecek oranda beyaz fayans çimentosu ilave edilerek sağlam ve sert bir zemin elde edilir. İnce katlar haline kullanılmalıdır.

Application Features

Thinning Ratio	Kullanıma hazırdır
Coverage (m ² /L)	Uygulama şekline ve uygulanan çatlağın genişliğine göre değişir.

Application Equipment

Spatule	Mala, spatula gibi macun çekme malzemeleri.
---------	---



A1 Akrilik Macun

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATIONS

Product Features	Standard
Drying Time (20 °C)	
Recoat (h)	12
Full dry (h)	1-3
<i>* The specified drying time; temperature, humidity, such media may vary depending on the application thickness and application conditions.</i>	
Poz No	
10.300.1202	

STORAGE and PACKAGING

Packaging Information	3 kg; 25 kg
Storage Conditions	It should be stored in a closed container without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep container closed when not in use. Preserve against freezing.

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. "Polisan Kansai Boya" has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication. It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.