



## Spray Varnish

### TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

It can be applied to many surfaces, fast drying, solvent based, decorative and protective, Glossy / matt spray varnish

### PRODUCT FEATURES

It can be used for both interior or exterior surface. It is unleaded, water repellent, UV resistant, scratching and impact resistant and pulverizing exit cleans it self. It doesn't include any harmful material for ozone layer.

### RECOMMENDED FOR

It is used for leisure purposes, decoration, bike, motorcycle, automobile applications.

### TECHNICAL SPECIFICATIONS

Sample Text	Standard	
View containing	-	
Smell	-	
Color	Transparant	
Gloss	-	
Gloss(60°)	-	
20 °C, Density	0,75-0,80	g / ml
20 °C, Pressure	4,0±0,5	bar
50 °C, Pressure	8,0±0,5	bar
Viscosity Ford Cup 4	11"-12,5"	
Flash Point	Below 0°C	
Teoric Cover Area(m <sup>2</sup> /400ml)	2,5-3	
Recomended Number of Layers	2-3	
Thicknes 1. Layer	17	micron
Thicknes 2. Layer	35	micron

\* The provided solids, viscosity and density data may vary depending on the color.

### Drying time

Dust-free dry	5-8	min
Touch dry	15-20	min
Recoat	15-20	min
Full dry	16-24	h

\* The provided drying time data are available in 23 °C ambient temperature and 50 ± 2 % relative humidity conditions.

### SURFACE PREPERATION AND APPLICATION

Before application, thoroughly shake the spray for a minimum of 1 minute. After unlocking the safety catch on the cover, keep the can upright and spray on the application surface from a distance of 25 cm.

**Surface Preparation:** Before application the surfaces should be cleaned from dust, dirt, humidity and grease and should be used a binder if required.

**Application:** Before application spray should be shaken as well and applied 2-3 times as thin layers from the distance 25 cm. There should be 20 minutes between the layer applications. After application, if there is paint remaining in can, the can should be reversed and press pulverizing part in order to use again later.



## Spray Varnish

### TECHNICAL DATA SHEET

#### STORAGE and PACKAGING

Packaging	400 ml
Storage Conditions	Should be stored in closed packs without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep packs closed when not in use. Preserve against freezing.
Shelf life	5 years

#### HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.  
Product of the safety data sheet should be treated by the rules.  
Refer to the nearest health facility for unexpected health problems.

#### LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. "Polisan Boya" has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication. It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.