



# TECHNICAL DATA SHEET

## ANTI-SILICONE ADDITIVE

### PRODUCT DESCRIPTION

#### General Information

Anti Silicone Additive, designed specifically to address common challenges encountered in surface preparation and finish quality. Residues from silicone, polish, wax, or grease can lead to issues such as "fish eyes" or cratering when applying coatings. Our Anti Silicone Additive effectively mitigates these problems, ensuring a smoother, more uniform finish. It's compatible with 2K paints and clear coats, making it an excellent addition to your coating processes.

#### Properties

Removes "fish eyes" (cratering)

It does not disrupt the physical and chemical properties of the product it is used for.

It is not used in primers and spacers.

### MIXING RATIO



**Product**

100 unit

**Anti-Silicone Additive**

1-1,5 unit

### SHELF LIFE



Unopened packing can stay minimum 1 year at room temperature.

### PACKING TYPES

0.250L

### HEALTH AND SAFETY DATA



Please follow the instruction mentioned on packs. Users should destroy the wastages according to the standards of health and safety regulations. For more information check the Material Safety Data Sheet.

The technical information contained in this sheet was prepared according to our applications, past experiences, and laboratory tests. Our company is not responsible for applications done outside the stated conditions and application errors that occur due to the user.

**Sintaş Boya ve Kimya Sanayi A.Ş.**

Tel: +90 282 725 25 35 (Pbx), Fax: +90 282 725 25 34  
info@sintas.com.tr , www.sintas.com.tr

