

PRODUCT DESCRIPTION

General Information	It is an auxiliary product used for removing all kinds of paints on iron, sheet metal and other metal surfaces.
Application areas	Dried old painted surfaces.
Properties	It is colorless. It can be applied to vertical surfaces without flowing.

PHYSICAL PROPERTIES

Color	Clear
Density (g/ml, 20°C)	1.00±0.05

APPLICATION DETAILS

Application Method



Brush, Roller

Scraping Time 15-20 minutes

Influence Duration 25-30 minutes

Surface Preparation



Sintaş Paint Remover is applied in a thick layer with a soft brush and spread on the surface.

The paint on the surface can be easily scraped off with a steel spatula.

If the paint to be removed is too thick and hard, the above application is repeated.

After the paint is completely removed, the surfaces are cleaned by washing with plenty of water.

Suggestions

Paint remover should be applied in well-ventilated areas.

It should not be applied to very hot surfaces.

It should not be applied to plastic surfaces.

It must be applied in the shade.



TECHNICAL DATA SHEET

PAINT REMOVER

SHELF LIFE



Unopened packing can stay minimum 1 year at room temperature.

PACKING TYPES

1 Kg / 20 Kg

HEALTH AND SAFETY DATA



Please follow the instruction mentioned on packs. Users should destroy the wastages according to the standards of health and safety regulations. For more information check the Material Safety Data Sheet.

The technical information contained in this sheet was prepared according to our applications, past experiences, and laboratory tests. Our company is not responsible for applications done outside the stated conditions and application errors that occur due to the user.

Sintaş Boya ve Kimya Sanayi A.Ş.

Tel: +90 282 725 25 35 (Pbx), Fax: +90 282 725 25 34
info@sintas.com.tr , www.sintas.com.tr

